PRESIDENT – THERMOSIPHONIC



MODEL:

FAEMA President Thermo 3 Buttons A2 FAEMA President Thermo 3Buttons A2 AS FAEMA President Thermo 3Buttons A3 FAFMA President Thermo 3Buttons A3 AS

ITEM:

F01-UP210D9BT999A F01-UP210D9BTG9BA 'F01-UP310D9BT999A F01-UP310D9BTG9BA

Date: Project:

Location:

CUSTOMIZATION

Unique design and new technology that never fails to assure great quality in every cup.



FEATURES



Temperature with Knobs



Smart Boiler



New Interface



New stainless steel portafilters

PGS

AutoSteam Milk 4 (optional)





Thermo Balance System with the NEW External Adjustable Temperature by group.

Choosing the most suited termic system is not easy.



Even More Exclusive

Design and style make the NEW President a truly unique machine. However, it is made even more exclusive by the endless customization options. The thermosiphon version is possible to customize the base and all the bodywork thanks to the easy-to-remove system.



Timeless style: the best coordination between the various stainless steel and black matt finishing for a unique character.

115 Matheson Blvd East, Mississauga, ON L4Z 1X8 Toll Free: 855.544.8600





That is why the New FAEMA President offers 2 versions: Thermosiphonic version that guarantees the termic regulation of each group; and a GTI version with independent coffee boilers.

TECHNICAL DATA



			(66) (66) (16)	1.5) pos.2= 145 (5.7)
			290 (11.4)	Customization Body & Base finishes
				В
	A2	RMOSIPHONIC PRESID	A4	-
Features	2	2	2	The machine Body (A)
Steam wands Hot water wands	1	1	1	
Hot water selections	3	3	3	Base Finishes (B)
Boiler capacity (L)	7	7	7	(A) Steel or Chrome
Electric cup warmer (3-temp settings)	\checkmark	\checkmark	\checkmark	(B) Matte Black
Technical Information				
Dimensions: Width x Depth x Height (mm)	820 x 630 x 505	1040 x 630 x 505	1260 x 630 x 505	
Weight (kg)	77	90	113	
Power at 220-240V~60Hz (W) 220-240V3~60Hz (W)	6200 - 7400	7500 - 8800	7500 - 8800	
				A2- Group A3- Group
	us 🐵 🤇 E		TRESIDENT	Receptacle Receptacle

Euro-Milan **Distributing** reserves the right to modify the characteristics of the products illustrated in this publication without prior notice for misprints and other errors. There may be colour deviations due to the printing process.



NEMA L6-30R

NEMA 6-50R