

## iMix iM 18

Spiral kneading machine for pizza, pastry and bakery.

Date	
Project	
Location	





## INTERNAL CONSTRUCTION

Motorization with bath oil motoreducer.

Chain drive.

Rotating transmission parts are assembled on self lubricating ball bearings.

Electrical equipment with low-voltage auxiliary circuit.

Safety device for grille.

## **OPERATION**

Dough homogenity and oxygenation by the combined rotating movement of the utensil and basin.

The shape of the spiral assures a low and constant temperature of dough during the working.

Possibility to mix maximum 18 Kg in few minutes.

## **EXTERNAL CONSTRUCTION**

Structure in powder painted stainless steel. Spiral, basin, dough-breaker and safety grille in stainless steel.

Thick frame to avoid vibrations in every working phase.

Push-button panel on the right side.

Machinery on rotating wheels.

## STANDARD EQUIPMENT

Spiral

Basin

Dough-breaker

Rotating wheels

Timer





# MORETTI FORNI


## **Technical Data**


## **iM 18**


**TOP VIEW** 

REAR VIEW

RIGHT SIDE VIEW







Note: The dimensions indicated in the views are in millimeters

### **SPECIFICATIONS**

Spiral kneading with firm head, ideal for small spaces with rotating wheels. To the construction are used height quality and robustness materials. Thanks to the particular shape of spiral and to the rotating movement of the utensil combined with that of the basin, the spiral kneading, gives possibility to mix in few minutes 18 Kg dough, and assures very good homogeneity and oxygenation. The model assure constant temperature of the dough from beginning to end working, so eliminate the danger of incidental overheating. The transmission system is particularly silent because all parts are assembled on waterthigt ball bearings with bath oil motoreducer, free maintenance. The machinery is provided of indispensables safety devices.

#### **TECHNICAL FEATURES**

## DIMENSIONS SHIPMENT INFORMATIONS FEEDING AND POWER

External height	680 mm	Packed machinery:		Standard feeding
External depth	680 mm	Max height	755 mm	A.C. V208 3ph Power 0.75 kW
External width	380 mm	Max depth		A.C. V230 1ph Power 0.88 kW
Weight	65 kg	Max width	480 mm	Frequency 60 Hz
	_	Weight	(65+5)kg	

#### **BASIN CAPACITY**

18 kg
20 lt
360 mm
210 mm
18 mm





Euro-Milan/ MORETTI FORNI S.P.A. reserves the right to modify the characteristics of the products illustrated in this publication without prior notice. We accept no liability for misprints and other errors. There may be colour deviations due to the printing process.



