

SPEED S +PLUS

MODEL:	ITEM:
ZUMEX Speed S+ Counter Top	Z0108825
ZUMEX Speed S+ All in One Wide Mirror	Z0108826-WM
ZUMEX Speed S+ All in One Wide Black	Z0108827-WB
ZUMEX Speed S+ All in One Narrow Mirror	Z0108828
ZUMEX Speed S+ Tank All in One	Z0108842

Date: _____

Project: _____

Location: _____

The fastest, most robust juicer.

Speed S+plus



Speed S+plus



Speed S+plus All-in-One



Speed S+plus Tank All-in-One

Three models that adapt to you

FEATURES



Original System®



1Step Kit



Antibacterial technology



The quietest juicer of all



Type of demand VERY HIGH



Quality and food hygiene guaranteed



- ① **1-STEP KIT:** QUICK REMOVAL OF JUICE EXTRACTION KIT - 10 SECONDS
- ② **HIGH-CAPACITY FEEDER (20 KG)**
- ③ **40 PIECES OF FRUIT PER MINUTE**
- ④ **DRAIN & CLEAN** FOR EASIER FEEDER CLEANING
- ⑤ **A 250ML JUICE IN 5 SECONDS**

An efficient, safe and impeccable service, designed to satisfy large juice demands. The new Speed S +plus models offer more features and better cleaning. Perfect for supermarket chains, hotels or self-service that seek a higher level.

Speed S +plus All-in-One

M 1Step Kit
65 - 81 mm

S 1Step Kit
45 - 67 mm

L 1Step Kit
75 - 95 mm

Two-position tray
for serving juice in
glasses or bottles, with
direct drain to the waste
buckets

**Resistant, lightweight
podium** with a capacity
of up to 100 litres, available
in two finishes and two
widths

2 Services tap
Non-continuous juice
flow when the tap is
pressed and continuous
flow when the automatic
dispensing mode
is selected



Speed S +plus Tank All-in-One

**Intelligent Touch
digital display**

PulpOut System
triple filtering with automatic
conveyor belt to remove the
pulp and optimize performance

5-litre tank

Available in 2 colours



Speed S +plus

Technical Characteristics

Output	120 kg/h - 1.8 l/min 264 ½ lb/hr - ½ gal/min	Net weight	15 kg 33 lbs
Speed	3500 / 4500 r.p.m.	Consumption	1.8 A
Fruit size	Less than 75 mm	Voltage	115 V 60 Hz
Dimensions	29 x 50 x 51 cm 11.4" x 19.7" x 20.1"	Power	870 W 1.17 HP
Waterproof specification	IPX1	Security	Double microswitch on handle and container. Safety detection and thermal protection system



Speed S +plus

Euro-Milan Distributing reserves the right to modify the characteristics of the products illustrated in this publication without prior notice for misprints and other errors. There may be colour deviations due to the printing process.

Receptacle



NEMA 5-15R