



CLEANING INSTRUCTIONS MINEX

Caution! For a correct cleaning process please follow the instructions below. Make sure machine is unplugged from electrical current.

Zumex recommends **cleaning the machine at least once or twice a day**, depending on how much it is used in order to maintain optimal food hygiene conditions.



Open the cover lock.



Release the twirler blade and support turning the blade lock 180°.



Unscrew and remove the securing knobs from the squeezing units.



Remove the peel container.



Release the tap by pressing its sides to loose the pins.



Open the cover and pull upwards. Remove the cover.



Once unlocked pull gently towards you. CAUTION! The blade is very sharp, be careful not to cut yourself.



Remove both the upper and lower securing knob.



Remove the juice container with its filter and tap.



Remove completely the tap to clean it.



Extract the retainer pulling out.



Remove the peel ejector pulling sideways.



Remove the juice jug.



Dismantle the juice filter from the juice container.

INFORMATION

All pieces, **EXCEPT THE FRONT COVER**, can be cleaned in a dishwasher.

The juice extraction zone and the front cover should be cleaned using a moist cloth and dish washing liquid. Rinse with clean water to remove any washing liquid traces.









CLEANING INSTRUCTIONS MINEX

Caution! For a correct cleaning process please follow the instructions below. Make sure machine is unplugged from electrical current.

To assemble the machine repeat the process in reverse and ready to work.



Assemble the tap in the juice container pressing its sides and placing correctly the pins.



Place the juice container with its filter and tap in its right place making sure it is well fitted.



Place de squeezing units.



Insert the twirler blade and support and place the security lock in disassembly position.



Place the retainer in the axis, make sure it is correctly fitted can move smoothly.



Make sure the tapis well fixed.



Place the peel container.



Place the securing knobs in the squeezing units.



Place the peel ejector inserting sideways in the pins.



Place the cover inserting the pins in the hinges.



Place the filter in its correct position.



Place the juice jug.



Tighten the securing knobs of the squeezing units.



Turn the blade lock 180° to fasten the assembly.



Place the cover and lock it.



