

Cleaning and disinfecting guideline



Speed S +plus

01. Introduction

Through this cleaning and disinfecting guideline guarantees an efficient, hygienic cleaning process, free from bacteria, even when the equipment is very dirty.

This guideline has been certified by an independent laboratory: *Speed S + Plus (v.00) cleaning instruction validation report performed by an independent laboratory with report number IFSC243/19Rev3.





For a correct maintenance of your Zumex juicer, careful cleaning it is essential.

Zumex suggests a daily and **thorough cleaning**, following these hygiene and disinfection guidelines for ensuring a good performance and durability of your juicer.

O2. Tools required for effective cleaning:

• Zumex Citric Active[™] detergent . specially designed for Zumex juicers and commercial juicers.

• Quaternary ammonium-based **disinfectant** specially certified against Covid-19

Zumex suggests:

- Suma Bac D10, Diversey
- Alcosan VT10, Diversey
- Desincol 2, Cleanity

• Clean or new **sponge /dishcloth** of a material that does not scratch the machine surfaces..

- Clean disposable **paper**.
- Wash point.

• **Brush*** supplied by Zumex for the cleaning points which require it.

*The brush must be cleaned and sanitised by following the instructions below.



03. Steps required for effective cleaning:

In the juice circulation zone, follow the specific steps to guarantee maximum hygiene:



1. Apply **Zumex Citric Active™** to remove wax and pulp. Leave to act 30 seconds and remove the dirt with a sponge.



3. Apply a **antibacterial cleaner** suggested by Zumex and leave to rest for 1 minute.

2. Rinse with water.

4. Clear with water and dry every nook and piece with disposable paper.





04.Disassembling the Juice Machine

Caution! For a correct cleaning process, please follow the instructions below. Before getting started, make sure that the machine is unplugged from main power.

- 1 Take off the feeder **basket**.
- 2 Take off the **feeder plate** by unscrewing the central knob.
- 3 Insert the long cleaning brush into the **Drain&Clean** hole in the base of the feeder, removing any residue that you may find in the tube.
- 4 Turn the knobs and take off the **front cover** as well as the side outputs.
- 5 Take off the **automatic PulpOut System**, by lifting the assembly with the part closest to you.
- 6 Remove the **2Services tap** by easily un-screwing it.
- 7 Remove the stainless-steel **peel chutes**.
- 8 Press the side tabs to remove the **juice tray.**
- 9 Unscrew the central knob of the **1Step Kit**.
- 10 Remove the **1Step Kit** by pulling it towards you with the stainless-steel handles.







7









10



The cleaning process for Speed S+plus will continue in the next page.



- 11 Place the blade protector before extracting the blade. Remove the **blade** by pulling the handle towards you.
- Caution! Be careful not to cut yourself.
- 12 Clean the **front** part of the machine and the feeder with Citric active and a soft sponge.
- 13 Remove the **waste baskets** from the base to empty them. Clean inside the **base** with a soft sponge.
- 14 Once all the parts have been disassembled, proceed to **deep clean** the machine.







14



Speed S +plus Cleaning instructions for components



Cleanliness and hygiene warnings

It is necessary to clean all parts that come into contact with the juice **each day**.



All the parts, with the exception of the cover and the tap, can be put in a **dishwasher** to clean them.



Cleaning of the machine and any of its removable parts must be done with a **sponge soaked in Citric Active soapy water**. Do not use scouring sponges that could scratch the surfaces.



It is necessary to sterilise the machine with a **disinfectant product** after each cleaning.



Rinse with plenty of water

after sterilising, in order to remove any remaining disinfectant. Dry carefully all the parts with disposable paper.

Zümex



Cleaning instructions for: **Removable components**

DAILY CLEANING

- 1 Clean the **blade**, **bottom filter**, **juice tray**, and **peel guides** piece by piece with soapy water and then rinse with clean water.
- 2 Remove the **side outputs** from the front cover.
- 3 Clean the side outputs and the **central part** of the cover with a soft sponge to avoid damaging the material. Rinse with plenty of water.
- 4 Clean the **feeding plate** with a soft sponge to remove the remaining particles still stuck to it.
- 5 Remove the upper part of the **tap** by twisting the matte thread.
- 6 Clean the tube and piston with the brush supplied with soapy water.















Cleaning instructions for components:

1Step Kit

To **clean quickly**, clean the 1Step Kit assembly in a single piece under a tap or in a dishwasher.

DAILY CLEANING

- 1 Clean the entire assembly with a sponge and Citric Active in a single piece under a tap. Move the **juicing heads** around to make sure that they are completely clean.
- 2 The assembly can also be washed in a single piece in a **dishwasher**.






Cleaning instructions for components: Automatic PulpOut System

DAILY CLEANING

- 1 Rest the PulpOut system on a flat surface and disassemble the **side cover**, holding it from above to remove the ends of the guides.
- 2 Remove the black **upper lid** by pushing upwards on the tabs sticking out.
- 3 Turn the assembly around and place your fingers on the **sweeping belt** by pushing it outwards to release it.
- 4 Remove the **sweeping belt** together with the other roller and remove both parts.
- 5 All the parts can be cleaned by hand with a soft sponge and soapy water.
- 6 All the parts can also be washed in a **dishwasher**.















Keep the filter clean

O MAINTAIN YOUR SELF-SERVICE STORE'S GOOD IMAGE.





Recommended cleaning instructions:

Cover, 1Step Kit, and PulpOut System

To clean the parts that have been removed, follow the general instructions for daily cleaning. MIDDAY CLEANING

- 1 Turn the knobs and take off the **front cover** as well as the side outputs.
- 2 Remove the **automatic PulpOut System** by lifting the assembly with the part closest to you.
- 3 Unscrew the central knob of the **1Step Kit**.
- 4 Remove 1Step Kit by pulling it towards you with the **stainless-steel handles**.
- 5 Place the blade protector before extracting the blade. Remove the **blade** by pulling the handle towards you.
- Caution! Be careful not to cut yourself.
- 6 Clean the **front area** of the machine with Citric Active and a soft sponge and rinse with a damp paper towel or water.















Replacing parts

For quick cleaning in the middle of the day, we recommend having a kit with spare parts. This Kit is made up of: cover, 1Step Kit, and PulpOut system.



Recommended cleaning instructions: **1Step Kit**

For **deep cleaning**, disassemble the 1Step Kit and clean all the parts.

WEEKLY CLEANING

- 1 Remove the **peel ejectors** located on the sides at the bottom.
- 2 The **knob** located on the lower central part.
- 3 Lift the **stainless-steel** handles.
- 4 Remove the **pressing units**.
- 5 Clean **all the parts** with a sponge and soap, rinse after with clean water. All the parts can also be washed in a **dishwasher**. To perfectly eliminate the wax inside the holes of pressing units, spray with Citric and wait 30 seconds before cleaning.







4





MACHINE DISASEMBLING is more easy with 1Step Kit





05.Assembling the Juice Machine

- 1 Ensure clean **waste baskets** is placed back into the podium.
- 2 Push the **blade** into the place.
- Important! Remove the blade protector before installing the 1Step Kit.
- 3 Slide **1Step Kit** into place.
- 4 Screw the central **knob** firmly into the centre of the **1Step Kit.**
- 5 Place the stainless-steel **peel chutes** onto the Juice Machine.
- 6 Place the **tap**.
- 7 Place the **automatic PulpOut System** back into place. Ensure it is lined up with the motor on the left hand side, as highlighted.
- 8 Place the **front cover** back into place.
- Place the **feeder plate** into position and screw the orange knob securely.
- **10** Place the **feeder basket** into place, twisting it firmly into the catch, as highlighted.



















10



Automatic PulpOut System assemble

- 1 Feed the sweeping belt through the gap of the metal casing until halfway through. Place a roller through the outside loop of the **sweeping belt**.
- Pull the sweeping belt and roller
 through until the roller rests onto the clip of the metal casing. Place the second roller through the inside loop of the sweeping belt.
- 3 Place the black **upper lid** into the metal casing, slotting into the groove as highlighted.
- 4 Firmly push down on the tabs of the black upper lid to secure it to the metal casing.



1

3

1









1Step Kit assemble

- 1 Rest the two circular upper pressing units, then the triangular lower pressing units, onto the **large metal part**.
- Ensure the larger holes of
 the pressing units are placed against the large metal part.
- Place the small metal part
 directly onto the pressing units. Once the parts are in place, screw the orange **knob** into the large metal part.

 Place both of the peel ejectors
 into the triangular lower pressing units. Ensure the clip secures onto the large metal part as highlighted above.







4



Zümex





115 Matheson Blvd East – Mississauga, ON L4Z 1X8 1.855.544.8600 905.501.8600 Fax: 905.501.9737 f 🖸 D

info@euromilan.com

euromilan.com

